

CoosAbsorb FT

CoosAbsorb™ FT is a fully-treated fluff pulp ideal for a wide range of airlaid and absorbent products. The Coosa Pines mill in Alabama produces fully bleached softwood kraft fluff pulp from the world's finest source of cellulose fibers – the pine forests of the U.S. South. The inherent characteristics and consistency of these fibers create uniformity, integrity, absorbency and wicking capabilities.

Coosa Pines fluff pulp is elemental chlorine-free (ECF) with bleaching sequence DEoDED. The mill's quality and environmental systems are ISO 9001 and ISO 14001 certified, respectively.

FLUFF

CoosAbsorb S

CoosAbsorb SL

CoosAbsorb SE

CoosAbsorb ST

CoosAbsorb FT

PHYSICAL PROPERTIES

BASIS WEIGHT	790 OD gsm
BRIGHTNESS	86% ISO
MOISTURE	9.0%
DENSITY	0.52 OD g/cc
FIBER LENGTH	2.7 (Kaj. FS-300, WAFL)
COARSENESS	25 (Kaj. FS-300, mg/100m)

FINISHED ROLL DIMENSIONS

WIDTH	10-60in	250-1525mm
DIAMETER	42-59in	1070-1500mm
CORE	3.0in	75mm
PACKAGING	Fully wrapped with stretch film	

FLUFF PROPERTIES

KAMAS ENERGY	34 kWh/t
FIBERIZATION	99%
PFI FLUID CAPACITY	9.4 g/g
PFI ABSORPTION RATE	5.6 g/sec